

DATA SHEET

12 V 11 EB



GENERAL SPECIFICATIONS

Model Number	K2B12V11EB
Average Operating Voltage @ C/5	12.8 V
Nominal Capacity @ C/5	11.1 Ah

MECHANICAL SPECIFICATIONS

Dimensions (L x W x H)	5.94 in x 2.53 in x 3.83 in
Weight	2.87 lb
Protection Control Module*	

TEMPERATURE SPECIFICATIONS

High Operating Temp	60 °C
Low Operating Temp	-20 °C

OTHER SPECIFICATIONS

Max Modules in Series	4
-----------------------	---

CHARGE SPECIFICATIONS

Charge Current	≤ 5.5 A
Charge Cutoff Voltage	14.6 V

DISCHARGE SPECIFICATIONS

Continuous Discharge	≤ 11.1 A
Discharge Cutoff Voltage	10.0 V
Pulse Discharge 30 Seconds	22.2 A



Manufactured and distributed by Grand Teton Energy Systems.


Performance may vary depending on application. All specifications and operating conditions are subject to change without notice. This data is provided for evaluation purposes only and does not imply any warranty or guarantee. Grand Teton Energy Systems all rights reserved.

Version 004 - Revised 12-02-2025

CONSTANT CURRENT TIME PROFILE @ 25 °C

C/20 (0.55 A)	20 hrs
C/2 (5.5 A)	2 hrs
1C (11.1 A)	60 min
2 C (22.2 A)	29 min
2.25 C (25 A)	27 min

DISCHARGE RATES @ 25 °C



BATTERY RECYCLE



NOTE: Do not mix with sealed lead-acid batteries when recycling. Refer to the Grand Teton user manual for proper operation.

BATTERY DIMENSIONS

