

DATA SHEET


12 V 22 EB



CONSTANT CURRENT TIME PROFILE @ 25 °C

C/20 (1.11 A)	20 hrs
C/10 (2.22 A)	10 hrs
C/5 (4.44 A)	5 hrs
C/2 (11.1 A)	2 hrs
1C (22.2 A)	1 hr

DISCHARGE RATES @ 25 °C



GENERAL SPECIFICATIONS

Model	K2B12V22EB
Average Operating Voltage @ C/5	12.8 V
Nominal Capacity @ C/5	22.2 Ah

MECHANICAL SPECIFICATIONS

Dimensions (L x W x H)	4.53 in x 3.52 in x 6.50 in
Weight	5.51 lb
Protection Control Module*	

TEMPERATURE SPECIFICATIONS

High Operating Temp	55 °C
Low Operating Temp	5 °C

OTHER SPECIFICATIONS

Max Modules in Series	2
-----------------------	---

CHARGE SPECIFICATIONS

Charge Current	≤ 5.55 A
Charge Cutoff Voltage	14.6 V

DISCHARGE SPECIFICATIONS

Continuous Discharge	≤ 11.1 A
Discharge Cutoff Voltage	10.0 V
Pulse Discharge 30 Seconds	25 A

Manufactured and distributed by Grand Teton Energy Systems.

Performance may vary depending on application. All specifications and operating conditions are subject to change without notice. This data is provided for evaluation purposes only and does not imply any warranty or guarantee. Grand Teton Energy Systems all rights reserved.

Version 003 - Revised 12-02-2025

BATTERY RECYCLE



NOTE: Do not mix with sealed lead-acid batteries when recycling. Refer to the Grand Teton user manual for proper operation.

BATTERY DIMENSIONS

