

DATA SHEET


24 V 11 EB



CONSTANT CURRENT TIME PROFILE @ 25 °C

C/20 (0.55 A)	20 hrs
C/2 (5.5 A)	2 hrs
1C (11.1 A)	60 min
2C (22.2 A)	30 min
2.25C (25 A)	25 min

DISCHARGE RATES @ 23 °C



GENERAL SPECIFICATIONS

Model	K2B24V11EB
Average Operating Voltage @ C/5	25.6 V
Nominal Capacity @ C/5	11.1 Ah

MECHANICAL SPECIFICATIONS

Dimension (L x W x H)	4.53 in x 3.52 in x 6.50 in
Weight	5.51 lb

TEMPERATURE SPECIFICATIONS

High Operating Temp (°C)	55 °C
Low Operating Temp (°C)	5 °C

OTHER SPECIFICATIONS

Parallel/Series Connection	3 Parallel / 8 Series
----------------------------	-----------------------

CHARGE SPECIFICATIONS

Charge Current	≤ 5.5 A
Charge Cutoff Voltage	29.2 V

DISCHARGE SPECIFICATIONS

Continuous Discharge	≤ 11.1 A
Discharge Cutoff Voltage	20.0 V
Pulse Discharge ≤ 30 seconds	40.0 A

GRAND TETON ENERGY SYSTEMS Manufactured and distributed by Grand Teton Energy Systems.

Performance may vary depending on application. All specifications and operating conditions are subject to change without notice. This data is provided for evaluation purposes only and does not imply any warranty or guarantee. Grand Teton Energy Systems all rights reserved.

Version 005 - Revised 03-19-2026

BATTERY RECYCLE



NOTE: Do not mix with sealed lead-acid batteries when recycling. Refer to the Grand Teton user manual for proper operation.

BATTERY DIMENSIONS

