

DATA SHEET

51 V 52 Ah - Replaces GC12



GENERAL SPECIFICATIONS

Model	GT51V52-GC12-SF-A20
Chemistry	LiFePO4
Nominal Voltage	51.2 V
Nominal Capacity	52 Ah
Nominal Energy	2560 Wh
Cycle Life	6000

MECHANICAL SPECIFICATIONS

Dimensions (L x W x H)	13.1 in x 6.9 in x 10.9 in
Weight	44 lb
Enclosure Protection	IP67

TEMPERATURE SPECIFICATIONS

Charge Temperature	0 °C to 55 °C
Discharge Temperature	-20 °C to 60 °C
Environmental Operating Temps.	-30 °C to 50 °C
Avoid Charging	< 0 °C

OTHER SPECIFICATIONS

Efficiency	99%
Communication	CAN bus
Parallel/Series Connection	16 Parallel / No Series

 Manufactured and distributed by Grand Teton Energy Systems.

Performance may vary depending on application. All specifications and operating conditions are subject to change without notice. This data is provided for evaluation purposes only and does not imply any warranty or guarantee. Grand Teton Energy Systems. All rights reserved.

Version 006 - Revised 05-30-2026

CHARGE SPECIFICATIONS

Charge Mode	CC-CV
Recommended Charge Current	25 A
Maximum Charge Current	50 A

DISCHARGE SPECIFICATIONS

Recommended Discharge Current	50 A Continuous
Discharge Cutoff Voltage	40 V
Peak Instant Discharge Current	200 A for 3 s
Recommended Low Voltage Disconnect	48 V

COMPLIANCE SPECIFICATIONS


Certification (Battery Pack)	CE UN38.3 MSDS
Shipping Classification	UN3480 Class 9

BATTERY RECYCLE



NOTE: Do not mix with sealed lead-acid batteries when recycling. Refer to the Grand Teton user manual for proper operation.

BATTERY DIMENSIONS



Easy Drop-in Replacement

